



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) Publication number: **0 293 472 B1**

(12) **EUROPEAN PATENT SPECIFICATION**

- (45) Date of publication of patent specification: **13.04.94** (51) Int. Cl.⁵: **A61B 17/22, A61B 17/32, A61B 17/36**
- (21) Application number: **86906951.8**
- (22) Date of filing: **27.11.86**
- (86) International application number:
PCT/JP86/00606
- (87) International publication number:
WO 88/03783 (02.06.88 88/12)

(54) **ULTRASONIC SURGICAL APPARATUS.**

- | | | | | | | | | | | | |
|--|------------------------|----------------------|------------------------|----------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|---|
| <p>(43) Date of publication of application:
07.12.88 Bulletin 88/49</p> <p>(45) Publication of the grant of the patent:
13.04.94 Bulletin 94/15</p> <p>(84) Designated Contracting States:
DE FR GB IT NL SE</p> <p>(56) References cited:</p> <table border="0"><tbody><tr><td>EP-A- 0 198 703</td><td>WO-A-83/01894</td></tr><tr><td>DE-A- 3 720 424</td><td>JP-A- 605 139</td></tr><tr><td>JP-A- 4 921 989</td><td>JP-A-60 116 347</td></tr><tr><td>JP-U- 6 055 408</td><td>JP-U- 6 055 409</td></tr><tr><td>US-A- 3 565 062</td><td>US-A- 3 792 701</td></tr></tbody></table> | EP-A- 0 198 703 | WO-A-83/01894 | DE-A- 3 720 424 | JP-A- 605 139 | JP-A- 4 921 989 | JP-A-60 116 347 | JP-U- 6 055 408 | JP-U- 6 055 409 | US-A- 3 565 062 | US-A- 3 792 701 | <p>(73) Proprietor: SUMITOMO BAKELITE COMPANY LIMITED
11-36 Mita-3-chome Minato-ku
Tokyo(JP)</p> <p>(72) Inventor: IDEMOTO, Morito
10-2-405, Ichiba-Kamicho
Tsurumi-ku, Yokohama-shi
Kanagawa 230(JP)
Inventor: NOGUCHI, Yasuo
70-17-709, Nasecho Totsuka-ku
Yokohama-shi
Kanagawa 245(JP)</p> <p>(74) Representative: Henkel, Feller, Hänzeler & Partner
Möhlstrasse 37
D-81675 München (DE)</p> |
| EP-A- 0 198 703 | WO-A-83/01894 | | | | | | | | | | |
| DE-A- 3 720 424 | JP-A- 605 139 | | | | | | | | | | |
| JP-A- 4 921 989 | JP-A-60 116 347 | | | | | | | | | | |
| JP-U- 6 055 408 | JP-U- 6 055 409 | | | | | | | | | | |
| US-A- 3 565 062 | US-A- 3 792 701 | | | | | | | | | | |

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

Description

TECHNICAL FIELD

The present invention relates to an ultrasonic surgical apparatus according to the preamble of claim 1 for crushing, sucking, and removing undesirable substances existing in the body, such as ulcerous tissue, thrombuses, calcification aggregates, by means of ultrasonic vibrations of a flexible ultrasonic probe.

BACKGROUND ART

Conventionally, as the methods of removing thrombuses, there are a method of inserting a catheter into a thrombus portion and dissolve the thrombus by injecting thereinto a thrombolytic agent such as streptokinase (e.g., Japanese Patent Unexamined Publication No. 57-173065); a method of withdrawing a catheter while maintaining the balloon of a balloon catheter in an expanded state and, at the same time, removing a thrombus (e.g., Japanese Patent Examined Publication No. 49-16472); and a method of clamping a thrombus portion by two expanded balloons, softening the thrombus by injecting a thrombolytic agent thereinto, and withdrawing a catheter and at the same time removing the thrombus (e.g., Published Japanese Translation of PCT Appln., Publication No. 58-501983).

However, even if the thrombolytic agent is injected locally through the catheter, there is a drawback in that the thrombolytic agent flows into normal terminal blood vessels and the like, thereby entailing the risk of hemorrhage in the terminal blood vessels and the like. Further, in the case where the catheter is withdrawn while maintaining the balloon of the balloon catheter in an expanded state to simultaneously remove the thrombus from the body, there was the risk of causing damage to the inner wall of a blood vessel since a safety measure against a tensile stress applied to the inner wall of the blood vessel has not been taken. In the case where a catheter provided with two balloons is used as a similar method of removing a thrombus, when a thrombus 27 is clamped by two balloons 31, 32 as shown in Fig. 7, the balloon 32 located closer to the tip of a catheter 30 needs to be inserted from a position 34 in front of a thrombus 27 up to a position 35 which is deeper than that of the thrombus 27, so that there was the danger of pushing, by the balloon 32, the thrombus 27 in the inserting direction 33, thereby moving the thrombus 27 to another part, such as a terminal blood vessel.

Furthermore, as a method of mechanically removing a thrombus, there is one in which a drill bit

is provided to the tip of a bar-like member, the drill bit is made to rotate by rotating the bar-like member, and the thrombus is crushed by the drill bit rotation. With this method, however, a torsional stress is applied to the inner wall of the blood vessel, so that there is a drawback in that the blood vessel may be cut off by the stress, and adjustment of the number of revolutions and the like is hence made difficult.

Further, recently, as a surgical apparatus using ultrasound, apparatuses are known in which an ultrasonic probe is connected to a source of ultrasonic vibration, tissue, a calcification aggregate, thrombus, or the like is crushed by mechanical vibrations of an ultrasonic frequency at the tip of the ultrasonic probe, and the crushed tissue, calcification aggregate, thrombus, or the like is removed through an inner hole provided in the ultrasonic probe (e.g., Japanese Patent Unexamined Publication Nos. 60-5139 and 49-21989). With such apparatuses, however, since the ultrasonic probe having a working portion which mechanically vibrates at an ultrasonic frequency is not flexible, there was a drawback in that it would be difficult to insert it into a curved blood vessel or a tubular tissue inside the body. Another prior art ultrasonic surgical apparatus comprising all the features of the preamble of claim 1 is known from US-A-3 065 062.

The present invention is aimed at removing the above drawbacks of the conventional methods of removing thrombuses as the fear of hemorrhage caused by a thrombolytic agent, the risk of causing damage to blood vessel owing to a tensile or torsional stress applied to the inner wall of the blood vessel by the balloon catheter, or the movement of the thrombus upon insertion of the balloon catheter, and also aimed at enabling to crush and remove a thrombus, a calcification aggregate or the like in the tubular tissue of a curved blood vessel or the like for which an operation has been difficult to conduct with the conventional ultrasonic surgical apparatuses. As a result of the diligent study, there was completed an ultrasonic surgical apparatus which is capable of allowing a flexible ultrasonic probe to be inserted directly into the affected part, crushing undesirable substances in the body such as a thrombus and a calcification aggregate by means of mechanical vibrations at an ultrasonic frequency, and removing the same by suction without affecting the normal surrounding tissue.

DISCLOSURE OF INVENTION

Namely, the present invention provides an ultrasonic surgical apparatus with the features of claim 1. Preferred embodiments of the ultrasonic surgical apparatus of the invention are described in

the subclaims.

BRIEF DESCRIPTION OF DRAWINGS

Fig. 1 is a view illustrating the overall construction of an ultrasonic surgical apparatus in accordance with an embodiment of the present invention; Fig. 2 is an enlarged diagram of a handpiece portion and illustrates the construction of the interior of a horn cover; Figs. 3(a) and 3(b) are enlarged views of a bellows portion, in which Fig. 3(a) shows a state in which the bellows portion is extended, while Fig. 3(b) shows a state in which the bellows portion is shrunk; Fig. 4 is a view illustrating an example of the configuration of the handpiece; Figs. 5(a) and 5(b) are views explaining an example of using the apparatus in accordance with the present invention; Figs. 6(a) and 6(b) are views illustrating an example of the cross-sectional structure of a flexible tube; and

Fig. 7 is a view illustrating a conventional method.

BEST MODE FOR CARRYING OUT THE INVENTION

Next, the invention will be described in detail with reference to the drawings. Fig. 1 is a view illustrating the overall construction of an ultrasonic surgical apparatus in accordance with an embodiment of the present invention. As shown in Fig. 1, the apparatus comprises four sections consisting of a section for generating mechanical vibrations of an ultrasonic frequency which is constituted by an oscillator 1 and a handpiece 36, a suction section constituted by a suction device 11 and a suction bottle 12, a liquid injecting section constituted by a liquid injector 14, and a catheter section constituted by a flexible tube 8 and branch tubes 7, 9, and 47.

High-frequency electric energy is supplied from the oscillator 1 to the handpiece 36 via cables 2, 3. The handpiece 36 is, as shown in Fig. 2, constituted from an ultrasonic vibration source 4, a horn 5, a horn cover 6, and an ultrasonic probe 17. The high-frequency electric energy is supplied to the ultrasonic vibration source 4, and the ultrasonic vibration source 4 generates mechanical vibrations of an ultrasonic frequency and the vibrations are transmitted to the horn 5. The mechanical vibrations are enlarged at the horn 5 and are transmitted to the ultrasonic probe 17.

The oscillator 1 has an oscillation circuit which is capable of supplying high-frequency electric energy corresponding to fluctuations in the state of the mechanical load of the horn 5 and the ultrasonic probe 17. Although 15 - 40 kHz is suitable as an oscillation frequency, 20 - 30 kHz is preferable

in view of the mechanical vibrations of the ultrasonic frequency and the crushing capability of the ultrasonic probe 17.

Although the connection between the ultrasonic vibration source 4 and the horn 5 is made by a screwing method, it is not limited thereto. The ultrasonic vibration source 4 is not particularly restricted insofar as it converts high-frequency electric energy of the magnetostriction type, the electrostriction type, or the like into mechanical vibrations. As the material of the horn 5, a metallic material which is capable of transmitting and enlarging the mechanical vibrations of an ultrasonic frequency and has a fatigue strength sufficient to withstand the mechanical vibrations is suitable, and stainless steel, duralumin, a titanium alloy, or the like is preferable.

Further, as a method of connecting the horn 5 and the ultrasonic probe 17, the screwing method, welding, or the like is suitable. The ultrasonic probe 17 is constituted by a fixing member 43 and a flexible linear transmitting member 44, and, as a method of connecting the fixing member 43 and the linear transmitting member 44, welding, adhesion, or the like is suitable. The materials of the fixing member 43 and the linear transmitting member 44 are not particularly limited if they are capable of transmitting the mechanical vibrations of an ultrasonic frequency and have a fatigue strength capable of withstanding the mechanical vibrations. However, the materials through which an X-ray cannot be transmitted are preferable, and a metallic material such as stainless steel, duralumin and a titanium alloy and a composite material such as carbon fiber-reinforced plastics are preferable. The horn cover 6 is provided around the horn 5 and the flexible ultrasonic probe 17. One end of the horn cover 6 is connected to the ultrasonic vibration source 4 by an appropriate method, while the other end thereof is connected to the branch tube 7 by means of an adhesive to retain airtightness. However, it is not limited to this connection method. The interior of the horn cover 6 is divided into partitioned chamber 23 and partitioned chamber 45 by means of a rubber O-ring 22, the rubber O-ring 22 being located at a node portion where the amplitude of the mechanical vibrations in the longitudinal direction 46 of the horn 5 is the minimum, and shielding the passage of the liquid. In addition, by providing a portion of the horn cover 6 with a bellows portion 10 formed of a flexible material, it is possible to move the branch tube 7 forth and back by virtue of the expansion and shrinkage of the bellows portion 10 in the longitudinal direction 46.

The ultrasonic probe 17 extends through the branch tube 7, and is disposed inside the inner hole of the flexible tube 8 shown in Fig. 1. As

shown in Fig. 3(a), the tip of the ultrasonic probe 17 has such a dimension that, when the bellows portion 10 is in an extended state, the tip will not protrude beyond the tip 16 of the flexible tube 8. By this structure, when the flexible tube 8 is inserted into the body, the tip of the ultrasonic probe 17 is located in the inner hole of the flexible tube 8, thereby making it possible to prevent a blood vessel or the like from being damaged by the tip of the ultrasonic probe 17.

Next, the suction device 11 is connected with the inner hole of the flexible tube 8 via the branch pipe 9, a changeover valve 13, the suction bottle 12, and tubes 38, 39, and 40, as shown in Fig. 1. Further, the liquid injector 14 is connected with the inner hole of the flexible tube 8 via the branch tube 47, a pipe 37, a changeover valve 15, and a tube 41. As a method of arranging the branch tubes 9 and 47, although Fig. 4 illustrates an example in which the branch tubes 9 and 47 are secured to the horn cover 6 by means of an appropriate adhesive, the arrangement of a configuration that facilitates the use by the operator is sufficient, not limited to the illustrated arrangement.

As for the method of using this apparatus, firstly, the partitioned chamber 23 and the inner holes 42, 20 are filled with a liquid which is not harmful to the bodily tissue, such as physiological saline solution, by an appropriate means so as to facilitate slippage of the linear transmitting member 44 installed inside the branch tube 7 and the flexible tube 8. For instance, a passage leading to the partitioned chamber 23 is provided on the side of the horn cover 6, a liquid such as physiological saline solution is injected into the partitioned chamber 23 and the inner holes 42, 20 through that passage, and the passage is then filled. Also, the inner suction hole 19 of the flexible tube 8 and the inner hole of the branch tube 9, communicating with the suction device 11, are filled with a liquid such as physiological saline solution by means of the operation of the suction device 11 and the changeover valve 13. With respect to the liquid injector as well, the branch tube 47 and the inner hole 20 are similarly filled with a liquid such as physiological saline solution.

Next, while confirming the position of the tip of the linear transmitting member 44 while projecting X-rays, the flexible tube 8 is inserted into the body and is inserted up to a portion to be operated on, e.g., a thrombus portion. For example, as shown in Fig. 5(a), a balloon 26 is provided in the vicinity of the tip 16 of the flexible tube 8. The balloon 26 is temporarily expanded using an inner hole (This inner hole is not illustrated, but when the balloon is used the inner hole similar to the inner hole 18, etc., is additionally provided.) provided in the flexible tube 8 for the balloon to such an extent that it

does not effect the flow of blood 24, so as to position the tip 16 since the flexible tube 8 sways owing to the flow of the blood inside a blood vessel 25. At this time, the mutual relationships between the flexible tube 8 and the linear transmitting member 44 are in the state shown in Fig. 3(a). Subsequently, by shrinking the bellows portion 10 in the direction of the arrow 28 while holding a part of the horn cover 6 on the side of the branch tube 7 in relation to the bellows portion 10, a working portion 21 of the ultrasonic probe 17 is made to project from the tip 16 of the flexible tube 8, as shown in Fig. 3(b). Hence, the balloon 26 is made shrunk after adjusting the position in relation to the thrombus 27. Then, as shown in Fig. 5(b), the ultrasonic probe 17 is mechanically vibrated at an ultrasonic frequency, the working portion 21 is brought into contact with the thrombus 27 to crush the thrombus 27. The small crushed pieces of the thrombus are sucked by the suction device 11 through the inner suction hole 19 shown in Fig. 6(a) and are removed out of the body. In addition, when the position of the thrombus 27 is unclear, a contrast medium or the like is injected through the liquid-injecting inner hole 18 shown in Fig. 6(a) by means of the liquid injector 14, and the above operation is carried out while confirming the position of the thrombus 27.

The material of the flexible tube 8 may be the one which is normally used for a medical catheter, such as soft vinyl chloride resin. On the other hand, the materials of the branch tubes 7, 9, and 47 are not particularly limited, but one which is capable of adhering with the flexible tube 8 is preferable. The inner hole and outer periphery of the flexible tube 8 and the inner holes of the branch tubes 7, 9, 47 are coated with an antithrombotic substance. As this antithrombotic substance, polyurethane, hydrogel, heparinated polymer, urokinase-coupled polymer, or the like is preferable, but the substance is not particularly restricted.

Furthermore, the number of the inner holes of the flexible tube 8 is not particularly restricted. For instance, even in the case where one inner hole 20 is provided as shown in Fig. 6(b), the inner hole 20 having the ultrasonic probe 17 can be used to make it communicate with the suction device 11 and the liquid injector 14 through a changeover valve.

An acute-angled portion is removed from the working portion 21 at the tip of the ultrasonic probe 17, so as to prevent damage of the inner wall of a blood vessel and the like. Although the configuration of an end surface thereof is not particularly restricted, oblique-angled or arcuate configuration is preferable.

Although the description has been made in detail here with respect to the case where the

apparatus is used for removal of a thrombus in a blood vessel as one embodiment according to the invention, the usage of the apparatus is not restricted to this and it goes without saying that the apparatus can be widely used for crushing and removing other undesirable substances in the body.

INDUSTRIAL APPLICABILITY

With the apparatus of the present invention, it is possible to insert an ultrasonic probe directly into the affected part where an undesirable substance, such as a thrombus, calcification aggregate, ulcer, or the like occurring in a narrow tubular tissue such as a bent blood vessel is present, and crush the undesirable substance by means of mechanical vibrations of an ultrasonic frequency and immediately remove the same out of the body without adversely affecting the normal surrounding tissue. Further, an incised portion at the body surface can be made only slightly larger than the diameter of a flexible tube enveloping an ultrasonic probe. Hence, an operation which gives a very low level of stress to the patient can be carried out within a short period of time and the burden on the patient after the operation can be alleviated significantly, so that the apparatus is suitable as an ultrasonic surgical apparatus.

Claims

1. An ultrasonic surgical apparatus including an ultrasonic vibration source (4) for generating ultrasonic vibrations, an oscillator (1) for supplying high-frequency electric energy to said ultrasonic vibration source, means (5) connected to said ultrasonic vibration source and adapted to transmit and amplify mechanical vibrations at an ultrasonic frequency, a suction device (11) for sucking and removing an undesirable substance from an operated part, an ultrasonic probe (17) comprising a flexible linear transmitting member (44) secured at one end to said means (5) adapted to transmit and amplify mechanical vibrations and having a working portion (21) at its other end adapted to effect mechanical vibration at said ultrasonic frequency, a flexible tube (8) having inner holes (18, 19, 20) and at least one branch tube (7, 9, 47) communicating with a respective one of said inner holes, said ultrasonic probe being disposed in one of the inner holes and said suction device being connected to one of the branch tubes, and means adapted to permit relative axial movement between the transmitting member (44) and the flexible tube (8) so that the working portion (21) protrudes beyond

the distal tip (16) of the flexible tube (8) or is located in said one inner hole, characterized in that

said means (5) connected to said ultrasonic vibration source and adapted to transmit and amplify mechanical vibrations of an ultrasonic frequency is a horn, said horn (5) having a cover (6) to which there is associated a bellows-like portion (10) made of a flexible material, the bellows-like portion (10) being connected to said flexible tube (8) and form said means to permit relative axial movement, and said flexible tube (8) has a balloon (26) in the vicinity of said working portion of said ultrasonic probe (17) disposed in another inner hole thereof, and said balloon being adapted to be expanded and shrunk through the another inner hole.

2. An ultrasonic surgical apparatus according to claim 1, wherein angled portions of said working portion (21) of said ultrasonic probe (17) are all oblique-angled or circular-arched in shape.
3. An ultrasonic surgical apparatus according to claim 1, wherein a liquid injector (14) for injecting an irrigation liquid is connected to one of said branch tubes of said flexible tube (8).
4. An ultrasonic surgical apparatus according to claim 1, wherein the surfaces of said inner hole in which said ultrasonic probe (17) is disposed and outer periphery of said flexible tube (8) are coated with an antithrombotic substance.

Patentansprüche

1. Chirurgische Ultraschallvorrichtung, umfassend eine Ultraschallschwingungsquelle (4) zum Erzeugen von Ultraschallschwingungen, einen Oszillator (1) zur Lieferung von elektrischer Hochfrequenzenergie zur Ultraschallschwingungsquelle, eine mit der Ultraschallschwingungsquelle verbundene Einheit (5), die mechanische Schwingungen auf einer Ultraschallfrequenz zu übertragen und zu verstärken vermag, eine Absaugvorrichtung (11) zum Absaugen und Beseitigen einer unerwünschten Substanz von einem operierten Teil, eine Ultraschallsonde (17) mit einem flexiblen, linearen Übertragungsglied (44), das am einen Ende an der Einheit (5) zum Übertragen und Verstärken mechanischer Schwingungen befestigt ist und an seinem anderen Ende einen Arbeitsabschnitt (21) aufweist, welcher mechanische Schwingung auf der Ultraschallfrequenz auszuführen vermag, einen flexiblen Schlauch (8) mit

inneren Öffnungen bzw. Durchgängen (18, 19, 20) und mindestens einem Verzweigungsschlauch (7, 9, 47), der mit einem betreffenden der inneren Durchgänge kommuniziert, wobei die Ultraschallsonde in einem der inneren Durchgänge angeordnet und die Absaugvorrichtung an einen der Verzweigungsschläuche angeschlossen ist, sowie eine Einrichtung zur Ermöglichung einer relativen Axialbewegung zwischen dem Übertragungsglied (44) und dem flexiblen Schlauch (8), derart, daß der Arbeitsabschnitt (21) über die distale Spitze (16) des flexiblen Schlauches (8) hinaus vorsteht oder sich in dem einen inneren Durchgang befindet,

dadurch gekennzeichnet, daß die mit der Ultraschallschwingungsquelle verbundene Einheit (5), die mechanische Schwingungen einer Ultraschallfrequenz zu übertragen und zu verstärken vermag, ein Schalltrichter ist, der Schalltrichter (5) eine Umhüllung (6) aufweist, welcher ein balgenartiger Abschnitt (10) aus einem flexiblen Werkstoff zugeordnet ist, der balgenartige Abschnitt (10) mit dem flexiblen Schlauch (8) verbunden ist und die Einrichtung zur Ermöglichung einer relativen Axialbewegung bildet, und der flexible Schlauch (8) einen in der Nähe des Arbeitsabschnitts der Ultraschallsonde (17) in einem anderen inneren Durchgang desselben angeordneten Ballon (26) aufweist, welcher Ballon über den anderen inneren Durchgang aufblasbar und zusammenziehbar ist.

2. Chirurgische Ultraschallvorrichtung nach Anspruch 1, wobei abgewinkelte Bereiche des Arbeitsabschnitts (21) der Ultraschallsonde (17) sämtlich von einem stumpf abgewinkelten oder kreisförmig gewölbten Form sind.
3. Chirurgische Ultraschallvorrichtung nach Anspruch 1, wobei ein Flüssigkeitsinjektor (14) zum Einspritzen einer Spülflüssigkeit an einen der Verzweigungsschläuche des flexiblen Schlauches (8) angeschlossen ist.
4. Chirurgische Ultraschallvorrichtung nach Anspruch 1, wobei die Oberflächen des inneren Durchgangs, in welchem die Ultraschallsonde (17) angeordnet ist, und der Außenumfang des flexiblen Schlauchs (8) mit einer antithrombotischen Substanz beschichtet sind.

Revendications

1. Instrument chirurgical à ultrasons comportant une source (4) de vibrations ultrasoniques pour générer des vibrations ultrasoniques, un oscil-

lateur (1) pour appliquer une énergie électrique haute fréquence à ladite source de vibrations ultrasoniques, des moyens (5) connectés à ladite source de vibrations ultrasoniques et adaptés pour transmettre et amplifier les vibrations mécaniques à une fréquence ultrasonique, un dispositif d'aspiration (11) pour aspirer et retirer une substance indésirable d'une partie opérée, une sonde ultrasonique (17) comprenant un élément (44) de transmission linéaire flexible fixé à une extrémité desdits moyens (5) adapté pour transmettre et amplifier les vibrations mécaniques et ayant une partie fonctionnelle (21) à son autre extrémité adaptée pour effectuer des vibrations mécaniques à ladite fréquence ultrasonique, un tube flexible (8) ayant des cavités internes (18, 19, 20) et au moins un tube de branchement (7, 9, 47) communiquant avec une cavité respective parmi lesdites cavités internes, ladite sonde ultrasonique étant disposée dans l'une des cavités internes et ledit dispositif d'aspiration étant connecté à l'un des tubes de branchement, et des moyens adaptés pour permettre le déplacement axial relatif entre l'élément (44) de transmission et le tube flexible (8) de telle sorte que la partie fonctionnelle (21) dépasse au-delà du sommet distal (16) du tube flexible (8) ou est située dans ladite cavité interne,

caractérisé en ce que

lesdits moyens (5) connectés à ladite source de vibrations ultrasoniques et adaptés pour transmettre et amplifier les vibrations mécaniques d'une fréquence ultrasonique sont constitués d'un cornet, ledit cornet (5) ayant un couvercle (6) auquel est associée une partie (10) en forme de soufflet constituée d'un matériau flexible, la partie (10) en forme de soufflet étant connectée audit tube flexible (8) et forme lesdits moyens pour permettre un déplacement axial relatif, et ledit tube flexible (8) comporte un ballon (26) à proximité de ladite partie fonctionnelle de ladite sonde ultrasonique (17) disposé dans une autre de ses cavités internes, ledit ballon étant adapté pour se dilater et se contracter par l'intermédiaire de l'autre cavité interne.

2. Instrument chirurgical à ultrasons selon la revendication 1, dans lequel les parties qui forment des angles de ladite partie fonctionnelle (21) de ladite sonde à ultrasons (17) ont toutes des formes à angle obtus ou circulaires.

3. Instrument chirurgical à ultrasons selon la revendication 1, dans lequel un injecteur de liquide (14) pour injecter un liquide d'irrigation est connecté à l'un des tubes de branchement

dudit tube flexible (8).

4. Instrument chirurgical à ultrasons selon la revendication 1, dans lequel les surfaces de ladite cavité interne dans laquelle est disposée ladite sonde ultrasonique (17) et la périphérie extérieure dudit tube flexible (8) sont revêtues d'une substance antithrombique.

5

10

15

20

25

30

35

40

45

50

55

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

